CAM-OPERATED SWITCH

B TYPE, BH TYPE

MOUNTING HOLE DIMENSIONS

B TYPE

			B	B-SN、SM	B-HC、TC、FC、SC	B-KMC	BL
H.T	Manual return						
S	Automatic return						
SB	Pushing and pulling						
SQ							
W	Dual body type						
BA-6	Lockout relay						
Mounting screw			M5×12 countersunk screws: 2	M5×12 countersunk screws: 2	M5×12 countersunk screws: 2	M4×12 countersunk screws: 2	M5×10 countersunk screws: 2

B-KM		B-KH		BM
Key: right	Key: bottom	Key: bottom	Key: right	
				H.T Manual return
				S Automatic return
				SB Pushing
M5×12 countersunk screws: 2	M5×10 countersunk screws: 2	M5×12 countersunk screws: 2	M5×10 countersunk screws: 2	M5×10 pan head screws: 2 / M5×12 countersunk screws: 2

BH TYPE

			BH	BHK	BHO	BHC
H.T	Manual return					Key: bottom / Key: right
S	Automatic return					
SB	Pushing and pulling					
SQ						
W	Dual body type					
BHE	Lockout relay					
Mounting screw			M5×10 countersunk screws: 2	M5×12 countersunk screws: 2	M4×12 countersunk screws: 2	M5×10 countersunk screws: 2

BHP		BHI	BHS、BHSB	BHM
Key: bottom	Key: right			
				H.T Manual return
				S Automatic return
				SB Pushing
M5×10 countersunk screws: 2		M5×10 countersunk screws: 2	M5×12 countersunk screws: 2	M5×10 pan head screws: 2 / M5×10 countersunk screws: 2