













CAM-OPERATED SWITCH

B TYPE, BH TYPE

MOUNTING HOLE DIMENSIONS

		B	B-SN, SM	B-HC, TC, FC, SC	B-KMC	BL
B TYPE	H.T	Manual return				
	S	Automatic return				
	SB	Pushing and pulling				
	SQ	Dual body type				
	W	Lockout relay				
BA-6	Lockout relay					
Mounting screw		M5×12 countersunk screws: 2	M5×12 countersunk screws: 2	M5×12 countersunk screws: 2	M4×12 countersunk screws: 2	M5×10 countersunk screws: 2
		B-KM	B-KH	BM		
Key: right		Key: bottom	Key: bottom	Key: right	H.T S SB	
						
M5×12 countersunk screws: 2		M5×10 countersunk screws: 2	M5×12 countersunk screws: 2	M5×10 countersunk screws: 2	M5×10 pan head screws: 2 M5×12 countersunk screws: 2	
BH TYPE	H.T	Manual return				
	S	Automatic return				
	SB	Pushing and pulling				
	SQ	Dual body type				
	W	Lockout relay				
BHE	Lockout relay					
Mounting screw		M5×10 countersunk screws: 2	M5×12 countersunk screws: 2	M4×12 countersunk screws: 2	M5×10 countersunk screws: 2	
		BHP	BHI	BHS, BHSB	BHM	
Key: bottom		Key: right			H.T S SB	
						
M5×10 countersunk screws: 2		M5×10 countersunk screws: 2	M5×12 countersunk screws: 2	M5×10 pan head screws: 2 M5×10 countersunk screws: 2		